

附件 2 浙江水利水电学院“南浔青年学者”申请表

姓名	宋源森	出生年月年龄 (年龄)	1993 年 7 月岁 (31 岁)	参加工作时间	2024 年 5 月
现所在单位 (部门)	机械工程学院	最高学历/学位	博士	专业技术职务	讲师
符合条款	符合科研类, 中科院 TOP1 区 1 篇, SCI 期刊论文 2 篇, 国内一级期刊 (浙大标准) 1 篇, 绩点 110				
· 所涉业绩	教学类 绩点: _____				
	科研类 绩点: <u>110</u>	Bai S X, Song Y S, Yang J. Elastic deformation of liquid spiral groove face seals operating at high speeds and low pressure[J]. International Journal of Mechanical Science, 2022. (中科院 TOP 一区期刊, IF: 7.3)			
		Song Y S, Bai S X, Yang J, et al. Fluid cavitation intensity in zero leakage upstream pumping face seals with spiral grooves[J]. International Journal of Applied Mechanics, 2023. (SCI 二区期刊, IF: 3.5)			
		Song Y S, Bai, S X. Thermal cavitation effect on the hydrodynamic performance of spiral groove liquid face seals[J]. Materials, 2024. (SCI 一区期刊, IF: 3.1)			
	人才称号类 绩点: _____	白少先, 宋源森. 液体密封端面倾斜椭圆孔上游泵送特性[J]. 摩擦学学报, 2019. (国内一级期刊 (浙大标准))			
总绩点	110				
备注: 请严格按照《浙江水利水电学院“南浔青年学者”实施办法(试行)》(浙水院〔2022〕114号)附件《业绩成果绩点赋值项目库》的类目、分类、等级(等次)、绩点填写。					
个人承诺	本人承诺上述所填内容真实、准确; 如有不实, 本人承担相应责任。 签名: <u>宋源森</u> 时间: <u>2024.11.29</u>				
以上部分由申请人填写, 所在单位审核。以下由单位(部门)和学校填写。					
所在单位 (部门) 意见	1.经审核, 申请人所填内容: <input type="checkbox"/> 属实 <input type="checkbox"/> 不属实; 2.是否符合所申请的类别: <input type="checkbox"/> 符合 <input type="checkbox"/> 不符合; 3.是否同意推荐: <input type="checkbox"/> 同意 <input type="checkbox"/> 不同意。 <div style="text-align: right;">负责人签名: _____ (部门盖章) _____年____月____日</div>				
科技处 审核意见	负责人签名: _____ (部门盖章) _____年____月____日	教务处 审核意见	负责人签名: _____ (部门盖章) _____年____月____日		
其他相关职能 部门审核意见	负责人签名: _____ (部门盖章) _____年____月____日				
学校意见	_____ (学校盖章) _____年____月____日				



论文检索报告

SCI-E 收录

根据宋源森提供的论文目录检索Web of Science™ 核心合集，其发表论文被 SCI-E 收录文献 3 篇（检索时间2024年11月19日）。

检索结果：被 SCI-E 收录文献 3 篇					
#	作者	标题	来源出版物	文献类型	入藏号
1	Song, YS; Bai, SX	Thermal Cavitation Effect on the Hydrodynamic Performance of Spiral Groove Liquid Face Seals	<i>MATERIALS</i> 2024, 17 (11): 2505.	J Article	WOS:0012 454677000 01
2	Song, YS; Bai, SX; Yang, J; Chen, JJ	Fluid Cavitation Intensity in Zero Leakage Upstream Pumping Face Seals with Spiral Grooves	<i>INTERNATIONAL JOURNAL OF APPLIED MECHANICS</i> 2023, 15 (10): 27.	J Article	WOS:0010 735762000 03
3	Bai, SX; Song, YS; Yang, J	Elastic deformation of liquid spiral groove face seals operating at high speeds and low pressure	<i>INTERNATIONAL JOURNAL OF MECHANICAL SCIENCES</i> 2022, 226: 107397.	J Article	WOS:0008 180039000 02
合计					3

备注 影响因子/期刊分区的年份选择：最新年份

收录文献附录

第 1 条，共 3 条：

标题：Thermal Cavitation Effect on the Hydrodynamic Performance of Spiral Groove Liquid Face Seals

作者：Song, YS (Song, Yuansen); Bai, SX (Bai, Shaoxian)

来源出版物：MATERIALS 卷：17 期：11 文献号：2505 出版年：JUN 2024

入藏号：WOS:001245467700001 PubMed ID: 38893770

文献类型：Article 出版物类型：J

作者地址：[Song, Yuansen; Bai, Shaoxian] Zhejiang Univ Technol, Inst Proc Equipment & Control Engn, Coll Mech Engn, Hangzhou 310032, Peoples R China.

所属机构：Zhejiang University of Technology

通讯作者地址：Bai, SX (corresponding author), Zhejiang Univ Technol, Inst Proc Equipment & Control Engn, Coll Mech Engn, Hangzhou 310032, Peoples R China.

电子邮件地址：songyuansen0704@163.com; bsx@zjut.edu.cn

出版商：MDPI 出版商城市：BASEL 出版商地址：ST ALBAN-ANLAGE 66, CH-4052 BASEL, SWITZERLAND

Web of Science 类别：Chemistry, Physical; Materials Science, Multidisciplinary; Metallurgy & Metallurgical Engineering; Physics, Applied; Physics, Condensed Matter

研究方向：Chemistry; Materials Science; Metallurgy & Metallurgical Engineering; Physics

IDS 号：UA9V0

eISSN: 1996-1944

基金资助机构和授权号：National Natural Science Foundation of China

基金资助致谢：No Statement Available

JCR 影响因子：

期刊	JCR 影响因子	指标年份
MATERIALS	3.1	2023

JCR 期刊分区：

数据库	JCR 学科类别	类别排序	类别分区	指标年份
SCIE	METALLURGY & METALLURGICAL ENGINEERING in SCIE edition	20/90	L45 Q1	2023
SCIE	MATERIALS SCIENCE, MULTIDISCIPLINARY in SCIE edition	208/439	Q2	2023
SCIE	PHYSICS, APPLIED in SCIE edition	63/179	Q2	2023
SCIE	PHYSICS, CONDENSED MATTER in SCIE edition	32/79	Q2	2023

SCIE	CHEMISTRY, PHYSICAL in SCIE edition	90/178	Q3	2023
------	--	--------	----	------

第 2 条, 共 3 条:

标题: Fluid Cavitation Intensity in Zero Leakage Upstream Pumping Face Seals with Spiral Grooves

作者: Song, YS (Song, Yuansen); Bai, SX (Bai, Shaoxian); Yang, J (Yang, Jing); Chen, JJ (Chen, Junjie)

来源出版物: INTERNATIONAL JOURNAL OF APPLIED MECHANICS 卷: 15 期: 10 提前访问日期: SEP 2023 出版年: DEC 2023

入藏号: WOS:001073576200003

文献类型: Article 出版物类型: J

作者地址: [Song, Yuansen; Bai, Shaoxian; Yang, Jing; Chen, Junjie] Zhejiang Univ Technol, Coll Mech Engn, Hangzhou 310032, Peoples R China.

所属机构: Zhejiang University of Technology

通讯作者地址: Bai, SX (corresponding author), Zhejiang Univ Technol, Coll Mech Engn, Hangzhou 310032, Peoples R China.

电子邮件地址: songyuansen0704@163.com; bsx@zjut.edu.cn; yangjing@zjut.edu.cn; zjut_chenjunjie@163.com

出版商: WORLD SCIENTIFIC PUBL CO PTE LTD 出版商城市: SINGAPORE 出版商地址: 5 TOH TUCK LINK, SINGAPORE 596224, SINGAPORE

Web of Science 类别: Mechanics

研究方向: Mechanics

IDS 号: AD0H6

ISSN: 1758-8251 **eISSN**: 1758-826X

基金资助机构和授权号: National Natural Science Foundation of China [51775504]

基金资助致谢: This work was financially supported by the National Natural Science Foundation of China [grant number 51775504].

JCR 影响因子:

期刊	JCR 影响因子	指标年份
INTERNATIONAL JOURNAL OF APPLIED MECHANICS	2.9	2023

JCR 期刊分区:

数据库	JCR 学科类别	类别排序	类别分区	指标年份
SCIE	MECHANICS in SCIE edition	51/170	Q2	2023

第 3 条, 共 3 条:

标题: Elastic deformation of liquid spiral groove face seals operating at high speeds and low pressure

作者: Bai, SX (Bai, Shaoxian); Song, YS (Song, Yuansen); Yang, J (Yang, Jing)

来源出版物: INTERNATIONAL JOURNAL OF MECHANICAL SCIENCES 卷: 226 文献号: 107397 提前访问日期: JUN 2022 出版年: JUL 15 2022

入藏号: WOS:000818003900002

文献类型: Article 出版物类型: J

作者地址: [Bai, Shaoxian; Song, Yuansen; Yang, Jing] Zhejiang Univ Technol, Coll Mech Engn, Hangzhou 310032, Peoples R China.

所属机构: Zhejiang University of Technology

通讯作者地址: Bai, SX (corresponding author), Zhejiang Univ Technol, Coll Mech Engn, Hangzhou 310032, Peoples R China.

电子邮件地址: bsx@zjut.edu.cn

出版商: PERGAMON-ELSEVIER SCIENCE LTD 出版商城市: OXFORD 出版商地址: THE BOULEVARD, LANGFORD LANE, KIDLINGTON, OXFORD OX5 1GB, ENGLAND

Web of Science 类别: Engineering, Mechanical; Mechanics

研究方向: Engineering; Mechanics

IDS 号: 2M9IE

ISSN: 0020-7403 **eISSN**: 1879-2162

基金资助机构和授权号: National Natural Science Foundation of China [51775504]

基金资助致谢: The research is financially supported by the National Natural Science Foundation of China (51775504).

JCR 影响因子:

期刊	JCR 影响因子	指标年份
INTERNATIONAL JOURNAL OF MECHANICAL SCIENCES	7.1	2023

JCR 期刊分区:

数据库	JCR 学科类别	类别排序	类别分区	指标年份
SCIE	ENGINEERING, MECHANICAL in SCIE edition	7/183	Q1	2023
SCIE	MECHANICS in SCIE edition	5/170	Q1	2023

注：以上检索结果经委托人确认。

浙江工业大学图书馆信息咨询部
教育部科技查新工作站（L45）
检索人：彭梅芳





宋源森
期刊指标综合报告

#	ISSN/EISSN	期刊	JCR影响因子 (最新年份)	JCR分区 (最新年份)
1	1996-1944	MATERIALS	3.1 (2023);	<ul style="list-style-type: none">CHEMISTRY, PHYSICAL [SCIE-Q3] 90/178 (2023);MATERIALS SCIENCE, MULTIDISCIPLINARY [SCIE-Q2] 208/439 (2023);METALLURGY & METALLURGICAL ENGINEERING [SCIE-Q1] 20/90 (2023);PHYSICS, APPLIED [SCIE-Q2] 63/179 (2023);PHYSICS, CONDENSED MATTER [SCIE-Q2] 32/79 (2023);
2	1758-8251	INTERNATIONAL JOURNAL OF APPLIED MECHANICS	2.9 (2023);	<ul style="list-style-type: none">MECHANICS [SCIE-Q2] 51/170 (2023);
3	0020-7403	INTERNATIONAL JOURNAL OF MECHANICAL SCIENCES	7.1 (2023);	<ul style="list-style-type: none">ENGINEERING, MECHANICAL [SCIE-Q1] 7/183 (2023);MECHANICS [SCIE-Q1] 5/170 (2023);

注：以上检索结果经委托人确认。

浙江工业大学图书馆信息咨询部
教育部科技查新工作站 (L45)
检索人：彭梅芳



Elastic deformation of liquid spiral groove face seals operating at high speeds and low pressure

Shaoxian Bai^{*}, Yuansen Song, Jing Yang

College of Mechanical Engineering, Zhejiang University of Technology, Hangzhou 310032, China

ARTICLE INFO

Keywords:

Liquid face seal
Elastic deformation
High speed
Cavitation effect
Sealing performance

ABSTRACT

The uneven distribution of fluid pressure in the spiral groove area leads to the elastic deformation of the seal faces, which not only affects the sealing performance but also affects the running stability. In this paper, a numerical model of a high-speed spiral groove liquid face seal is proposed with the consideration of elastic deformation and cavitation medium compressibility. The novelty of this study is that the pressure of the cavitation region is modeled as an uneven distribution rather than as a constant. This uneven pressure distribution of sealing surfaces is generally regarded to have an influence on face deformation. Based on the assumption that the fluid exists at a complete gas state in the cavitation, the elastic deformation and pressure distribution of sealing surfaces are calculated. The influence of elastic deformation on sealing performance is further investigated. Results show that the elastic deformation of sealing surfaces and cavitation effect has a significant influence on the stability of sealing clearance, which may produce a negative effect on the sealing performance of liquid face seals. The face deformation causes a divergent gap between two seal faces. With the increase of rotational speed, the elastic deformation of sealing surfaces reduces at low seal pressure but increases at higher seal pressure, which may influence the cavitation behavior and pressure distribution of surfaces. Furthermore, the sealing performance of spiral groove liquid face seal becomes more complicated because of the coupling effect of cavitation effect and elastic deformation. The changing trend of sealing performance is different under various seal clearance and seal pressure. The obtained results may provide guidance for the future design of liquid face seals in engineering applications under high-speed conditions.

1. Introduction

The liquid spiral groove face seal, as a kind of non-contact shaft seal, has been widely used in rotating machinery [1–4]. Generally, due to the hydrodynamic effect of face spiral grooves [5], a micron-scale clearance is generated to separate the seal faces of the rotor and stator during the operation [6]. The stability of this clearance between the seal faces is the key to ensuring the safe and reliable operation of the seal. However, this stable clearance is easily influenced by the elastic deformation of sealing surfaces [7–14], which may have a significant impact on sealing performance and even result in sealing failure, especially considering the cavitation effect [15–17]. More attention has been attracted to investigating the elastic deformation of sealing surfaces, which is beneficial to predicting sealing performance and optimizing the design.

In 1999, Baheti and Gkirk [18] analyzed the ring distortion of a high-pressure liquid seal and noted that the pressure difference between the inside and outside of the seal ring was the main cause of mechanical

deformation, and this deformation was conical. When the supply pressure was 1.48 MPa, the vertical deflection of the inside and outside of the seal ring were 0.0009 and 0.0080 mm, respectively. With the growth of seal pressure, the deflection demonstrated a similarly increasing trend. Afterward, the thermoelastohydrodynamic analysis of radial conical mechanical seals was conducted by Thomas et al. [19,20] and the results showed that the surface deformation significantly changed the geometric shape and sealing performance of gas face seals. Elastic deformation could cause convergence deformation of seal clearance and change the pressure field.

In addition, the groove arrangement of sealing surfaces also presents a significant influence on the sealing characteristics of liquid face seals. For example, a numerical analysis was conducted by Luo [21] to study the effect of waviness, taper, and groove type on the sealing performance. This study showed that the groove position arrangement had different influences on the opening force under the influence of the change of face structure. Alfredo [22] adopted the experimental method to investigate the deformation behavior of gas face seals under different

^{*} Corresponding author.

E-mail address: bsx@zjut.edu.cn (S. Bai).

<https://doi.org/10.1016/j.ijmecsci.2022.107397>

Received 10 January 2022; Received in revised form 16 May 2022; Accepted 24 May 2022

Available online 26 May 2022

0020-7403/© 2022 Elsevier Ltd. All rights reserved.

INTERNATIONAL JOURNAL OF MECHANICAL SCIENCES

ISSN: 0020-7403

Review: 否

大类及分区

工程技术 1 区 Top

小类及分区

ENGINEERING, MECHANICAL 工程：机械 1 区

MECHANICS 力学 1 区

Fluid Cavitation Intensity in Zero Leakage Upstream Pumping Face Seals with Spiral Grooves

Yuansen Song^{*}, Shaoxian Bai[†], Jing Yang[‡]
and Junjie Chen[§]

*College of Mechanical Engineering
Zhejiang University of Technology
Hangzhou 310032, P. R. China*

**songyuansen0704@163.com*

†bsx@zjut.edu.cn

‡yangjing@zjut.edu.cn

§zjut_chenjunjie@163.com

Received 27 February 2023

Revised 2 July 2023

Accepted 21 August 2023

Published 25 September 2023

Cavitation intensity variations in fluid lubrication may alter the mechanical and lubrication properties of the fluid. In this paper, a compressible cavitation model is presented to study the effect of fluid cavitation intensity on zero-leakage flow of upstream-pumping spiral grooves face seals (UPSGLFS). The pressure variation in cavities can be calculated considering the compressibility of the lubricating medium, the ratio of minimum pressure to cavitation pressure is further defined to characterize the cavitation intensity. A numerical analysis of the zero-leakage behavior of UPSGLFS is then performed based on its effect. Results show that cavitation plays a negative role in sealing performances. However, the groove's configuration and working conditions have substantial effects on controlling the cavitation intensity. Meanwhile, whether a circumferential continuous pressure ring above the seal pressure can be formed is the design basis for judging the strict zero leakage of the medium, rather than only depending on the change of leakage rate parameter value. With suitable spiral groove parameter design, zero-leakage design for upstream-pumping seals may be achieved under multi-speed and multi-seal-pressure conditions. Here, a zero-leakage map is presented for working conditions with multi-speed ranging from 500 to 20,000 rpm and multi-seal pressure ranging from 0.1 to 3.0 MPa.

Keywords: Liquid lubrication; fluid cavitation intensity; zero leakage; upstream pumping flow; spiral groove seal.

1. Introduction

Upstream pumping face seals, in particular liquid spiral-groove face seals, have been widely applied to strictly control medium leakage, so as to ensure the reliable and safe operation of petroleum, petrochemical, and aerospace power equipment

[†]Corresponding author.

Article

Thermal Cavitation Effect on the Hydrodynamic Performance of Spiral Groove Liquid Face Seals

Yuansen Song  and Shaoxian Bai *

Institute of Process Equipment and Control Engineering, College of Mechanical Engineering, Zhejiang University of Technology, Hangzhou 310032, China; songyuansen0704@163.com

* Correspondence: bsx@zjut.edu.cn

Abstract: Cavitation in micro-scale lubricating film could be determined by the fluid's thermal properties, which impacts the hydrodynamic lubrication capacity dramatically. This study aimed to novelly investigate the impact of the thermal cavitation effect on the hydrodynamic performance of liquid face seals, employing the compressible cavitation model, viscosity–temperature effect, and energy equation. The finite difference method was adopted to analyze the thermal cavitation by calculating the pressure and temperature profiles of the lubricating film. The working conditions and geometric configuration of liquid face seals under different thermal cases were further studied to explore their effects on sealing performance. The results showed that thermal cavitation could reduce the temperature difference of liquid film at high speeds, and cavitation would be weakened under temperature gradients, which further dropped off the hydrodynamic performance. Contrary to the leakage rate, the opening forces tended to be lower with the increasing seal pressure and film thickness under high-temperature gradients. Furthermore, apart from the spiral angle of grooves, the hydrodynamic performance exhibited significant variation with increasing groove depth, number, and radius at high-temperature gradients, which meant that the thermal cavitation effect should be considered in the design of geometric grooves to obtain better hydrodynamic performance.

Keywords: thermal cavitation effect; liquid lubrication; hydrodynamic performance; cavitation; liquid face seals



Citation: Song, Y.; Bai, S. Thermal Cavitation Effect on the Hydrodynamic Performance of Spiral Groove Liquid Face Seals. *Materials* **2024**, *17*, 2505. <https://doi.org/10.3390/ma17112505>

Academic Editor: Pawel Pawlus

Received: 17 April 2024

Revised: 14 May 2024

Accepted: 21 May 2024

Published: 23 May 2024



Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

The liquid face seal [1–3] (LFS), serving as a critical element in rotary power machinery, can ensure the long life and reliable operation of the equipment as a result of the hydrodynamic performance of lubricating film improved by the surface textures (such as spiral grooves [4], dimples [5], etc.). Meanwhile, cavitation is a complex mechanism in the lubrication analysis due to various inducing factors and the weakened hydrodynamic performance produced, especially at high speeds [6,7]; and its complexity further increases when the thermal properties of the cavitation medium are involved [8,9]. In the current engineering practice, the equipment gradually develops for high working parameters (high speed, high temperature, etc.), and the thermal cavitation effect cannot be ignored to better predict the serviceability and optimize the design.

In fact, the behavior of the seal can be significantly influenced by thermal effects at high rotation speeds. For example, the utilization of thermocouples integrated within the stationary ring, as demonstrated by Denny [10] in 1961, revealed a significant increase in facial temperature by several tens of degrees. In addition, Orcutt [11] employed a pyrometer to conduct temperature measurements of the rotor surface. The observed temperature gradient along the radial direction could exceed 10 K. The above findings were subsequently validated by Tournerie et al. [12] through the utilization of thermography as a technique. As observed by Doust and Parmar [13], a small inclination of the sealing ring happened due to the variations in surface temperature, resulting in their acquisition of a tapered

DOI: 10.16078/j.tribology.2018070

液体密封端面倾斜椭圆孔上游泵送特性

白少先*, 宋源森

(浙江工业大学 机械工程学院, 浙江 杭州 310032)

摘要: 气液异相介质隔离密封的实现有赖于密封端面几何型槽的上游泵送特性, 为探索多孔端面实现液封气密封的设计途径, 对液体密封端面倾斜椭圆孔上游泵送特性开展研究. 考虑空化效应, 采用有限差分方法对转速、密封间隙、密封压力等操作参数和孔深、倾斜角、方向因子、孔数等结构参数对开启力和泄漏率的影响规律进行了数值分析. 结果显示: 液体润滑条件下端面倾斜椭圆孔可产生明显的上游泵送效应, 增加周向孔数和方向因子可实现被密封介质的完全零泄漏, 同时可产生明显的流体动压效应使端面开启力提高50%以上. 文中密封压力条件下, 孔深取5~10 μm , 倾斜角取45°, 周向孔数大于80, 方向因子大于3时, 密封可实现完全反向泵送, 反向泄漏率的增加与随着孔数、方向因子和孔深的增加而增加.

关键词: 端面密封; 液体润滑; 椭圆孔; 上游泵送; 空化效应

中图分类号: TH117.2

文献标志码: A

文章编号: 1004-0595(2019)01-0010-07

Upstream Pumping Characteristic of Inclined-Ellipse-Dimples on Liquid-Lubricated Seal Face

BAI Shaoxian*, SONG Yuansen

(College of Mechanical Engineering, Zhejiang University of Technology, Zhejiang Hangzhou 310032, China)

Abstract: The realization of the gas-liquid heterogeneous medium isolation seal depends on the upstream pumping characteristics of the geometric groove of the sealing face. In order to explore the design approach of the liquid sealing gas seal for the porous face, the upstream pumping characteristic of inclined-ellipse-dimples on liquid seal face was theoretically analyzed. Considering the cavitation effect, the finite difference method was used to numerically analyze the influences of operating parameters (e.g. rotation speed, seal clearance and seal pressure) and the structural parameters (e.g. dimple depth, inclination angle, slender ratio and dimple number on the open force and leakage rate). Results show that the inclined-ellipse-dimple liquid face seals may present significant upstream pumping and hydrodynamic effects, which led to open force improved more than 50% greater in the analysis. A complete backward leakage may be achieved by the inclined-ellipse-dimple upstream pumping face seals by increasing dimple number and slender ratio. A complete backward leakage can be achieved under pressure condition in the cases of 5~10 μm dimple depth, 45° inclination angle, greater than 80 dimple number and greater than 3 slender ratio. Meanwhile, the increase in reverse leakage rate increased with the dimple number, slender ratio, and dimple depth.

Key words: face seal; liquid lubrication; ellipse-dimples; upstream pumping; cavitation effect

发动机等动力机械装备密封处于复杂的油、气工作介质环境, 通过端面型槽的上游泵送作用将油液或气体从低压侧泵送到高压侧可实现对油、气介质的有

效隔离, 即实现“油封气”或“气封液”异相流体密封, 而采用微孔型槽设计有利于进一步提高密封端面的耐磨性. Lebeck^[1]的直线槽上游泵送密封试验研究表明,

Received 29 June 2018, revised 22 September 2018, accepted 30 October 2018, available online 28 January 2019.

*Corresponding author. E-mail: bsx@zjut.edu.cn, Tel: +86-13738194311.

The project was supported by the National Natural Science Foundation of China (51775504).

国家自然科学基金项目(51775504)资助.

证 明

兹证明我院 2019 级博士研究生宋源森（身份证号码：
370304199307043512）博士生导师为白少先老师，特此证明！



博士学位证书

宋源森，男，1993年7月4日生。在浙江工业大学

化工过程机械

学科(专业)已通过博士学位的课程

考试和论文答辩，成绩合格。根据《中华人民共和国学位条例》的规

定，授予工学博士学位。

浙江工业大学

校长

学位评定委员会主席

高翔



证书编号:

1033722024100009

二〇二四年

一月二十三日

博士研究生 毕业证书



研究生 宋源森 性别 男

一九九三年七月四日生，于一九一六

年九月至二〇二四年一月在

化工过程机械 专业

全日制学习，学制五年，修完博士研

究生培养计划规定的全部课程，成绩合格，

毕业论文答辩通过，准予毕业。

校长：高翔

培养单位：浙江工业大学

二〇二四年六月二十三日

编号：103371202401000011

浙江工业大学印制

查询网址：<http://www.chsi.com.cn>